

TECHNICAL DATA

easy-on protective wall coating

Description

A clear protective coating that can be applied to all surfaces to provide durability to existing coatings, protection of bare substrates and exceptional graffiti resistance.

Benefits

- › Hard wearing finish cleans 100's of times
- › Protects painted walls for up to 20 years
- › Simple application
- › Resists graffiti
- › Easily cleaned – Spray paints, permanent markers, felt tip, ball-point pen etc just wipe off
- › Single coat = low applied cost
- › Can be applied over existing base coats and decorative finishes
- › Resistant to damage from repetitive cleaning operations
- › Low VOC – safe and virtually odourless
- › Non flammable
- › Class 'O' fire rating
- › Does not contain Isocyanates
- › Graffiti removed with safe removers and water
- › Cost effective
- › Resists mould and fungi
- › Does not support growth of MRSA, Salmonella, Listeria, E Coli etc.

Application

- › Coating is used UNDILUTED
- › Spray, brush or roller
- › Ensure total coverage of all areas to be protected

Equipment

Brush, roller or spray (Conventional or Airless)

Health & Safety

See separate Health & Safety Data / MSDS Sheet

Physical data

Colour	Transparent
Finish	Sheen
Substrates	Concrete, tile, mortar, existing coatings, plaster, brick and metals, timber, etc.
Components	2 (resin + cure)
Curing mechanism	Chemical reaction between components
Dry film thickness	25 - 50 microns
Number of coats	1 (usually)



easy-on
PROTECTIVE COATING

Physical data

Moisture permeability	35gm/ m2/24 hours
SG of mixed product	1.10 kg/L
VOC content	<8% weight
Calculated coverage	33 m2 per litre @ 25 microns
Practical coverage	9 - 33 m2

Dependant upon application losses, surface irregularities, porosity, waste, etc

Application	By brush, roller, low pressure airless/airmix or conventional spray equipment.
Environmental conditions	Air temperature 5°C to 50°C
Surface temperature	5°C to 45°C
Material temperature	5°C to 40°C
Relative humidity	>40%

To prevent condensation during application, surface temperature must be at least 3°C above dew point.

Pot life*	4 hours at 20°C
Touch dry*	4 hours @ 20°C (@25 microns dft)
Full chemical cure**	7 days
Storage life	12 months in cool, dry place in sealed containers
Equipment Cleaner	Xylene
Inflammable	no
Flash point	Resin > 97°C Cure > 96°C
Packaging	
Resin	3.75 l in 5 litre can
Cure	750ml in 1 litre can

* Pot life and touch dry times depend on temperature and quantities mixed.

** Do not attempt to clean the coating with any chemical until it has fully cured (7 days at 20°C)



solutions for the environment

T: 1300 763 335

www.environmentalcoatings.com.au